



N2XH 0,6/1 kV, CHKE-R, CXKE-R 0,6/1 kV

- 0,6/1 kV
- 4 kV
- ()

DIN VDE 0295 1, 2 IEC 228 1 2

C

DIN VDE 0207, 5

0,6/1 V / 4 kV

DIN VDE 0295 1 IEC 228 ^{+20 °C} 1

DIN VDE ()

4 x
12 x

-40 °C / +70 °C
- 5 °C / +50 °C

DIN VDE 0472, 813 C C DIN VDE 0472, 804 IEC 332-3
DIN VDE 0472, 816 IEC 1034-1

DIN VDE 0276

n x ² / /

1 X 4re	6,0	38,0	75,0
1 X 6re	7,0	58,0	97,0
1 X 10re	8,0	96,0	140,0
1 X 16rm	9,0	154,0	202,0
1 X 25rm	11,0	240,0	302,0
1 X 35rm	12,0	336,0	397,0
1 X 50rm	13,0	480,0	523,0
1 X 70rm	15,0	672,0	746,0
1 X 95rm	17,0	912,0	987,0
1 X 120rm	18,0	1.152,0	1.214,0
1 X 150rm	21,0	1.440,0	1.536,0
1 X 185rm	23,0	1.776,0	1.888,0
1 X 240rm	26,0	2.304,0	2.474,0
1 X 300rm	28,0	2.880,0	2.946,0
3 X 1,5re	10,0	43,0	153,0
3 X 2,5re	11,0	72,0	210,0
3 X 4re	12,0	115,0	263,0
3 X 6re	13,0	173,0	341,0
3 X 10re	15,0	288,0	490,0
3 X 16rm	18,0	461,0	730,0
4 X 1,5re	11,0	58,0	181,0
4 X 2,5re	12,0	96,0	236,0
4 X 4re	13,0	154,0	320,0
4 X 6re	14,0	230,0	419,0
4 X 10re	16,0	384,0	615,0
4 X 16rm	20,0	614,0	921,0
4 X 25rm	24,0	960,0	1.403,0
4 X 35rm	27,0	1.344,0	1.857,0
4 X 50rm	31,0	1.920,0	2.465,0
4 X 70rm	36,0	2.688,0	3.512,0
4 X 95rm	41,0	3.648,0	4.703,0

n x ² / /

5 X 1,5re	12,0	72,0	214,0
5 X 2,5re	13,0	120,0	278,0
5 X 4re	14,0	192,0	377,0
5 X 6re	16,0	288,0	503,0
5 X 10re	18,0	480,0	739,0
5 X 16rm	22,0	768,0	1.129,0
5 X 25rm	27,0	1.200,0	1.702,0
7 X 1,5re	12,0	101,0	256,0
7 X 2,5re	14,0	168,0	344,0
10 X 1,5re	15,0	144,0	258,0
10 X 2,5re	17,0	240,0	484,0
12 X 1,5re	16,0	173,0	397,0
12 X 2,5re	18,0	288,0	542,0
14 X 1,5re	17,0	202,0	440,0
19 X 1,5re	18,0	274,0	548,0
24 X 1,5re	22,0	346,0	713,0
30 X 1,5re	23,0	432,0	833,0
33 X 2,5re	24,0	792,0	1.302,0