



N YY-J() 0,6/1 kV, AYKY-J(O) 0,6/1 kV

- 0,6/1 kV
- 4 kV
-
-
- - ()
- 73/23/EWG CE ()
-

DIN VDE 0295 1, 2 IEC 228 1 2

DIN VDE 0207, 5

0,6/1 V

4 kV

DIN VDE 0295 1, 2 IEC 228 ^{+20 °C} 1, 2

DIN VDE ()

12 x

-40 °C / +70 °C
- 5 °C / +50 °C

B DIN VDE 0472, 804 IEC 332-1

DIN VDE 0271 IEC 502

n x ² / /

3 X 25rm/16re	25,0	874,0	1.575,0
3 X 35sm/16re	26,0	1.162,0	1.700,0
3 X 50sm/25rm	30,0	1.680,0	2.325,0
3 X 70sm/35sm	35,0	2.352,0	2.900,0
3 X 95sm/50sm	37,0	3.216,0	3.900,0
3 X 120sm/70sm	42,0	4.128,0	4.900,0
3 X 150sm/70sm	47,0	4.992,0	5.800,0
3 X 185sm/95sm	51,0	6.240,0	7.400,0
3 X 240sm/120sm	59,0	8.064,0	9.700,0
3 X 300sm/150sm	66,0	10.080,0	12.000,0
4 X 1,5re	13,0	58,0	220,0
4 X 2,5re	14,0	96,0	300,0
4 X 4re	16,0	154,0	410,0
4 X 6re	17,0	230,0	520,0
4 X 10re	19,0	384,0	720,0
4 X 16re	22,0	614,0	1.050,0
4 X 25rm	26,0	960,0	1.650,0
4 X 35sm	28,0	1.344,0	1.860,0
4 X 50sm	31,0	1.920,0	2.500,0
4 X 70sm	35,0	2.688,0	3.300,0
4 X 95sm	38,0	3.648,0	4.500,0
4 X 120sm	42,0	4.608,0	5.500,0
4 X 150sm	47,0	5.760,0	6.880,0
4 X 185sm	52,0	7.104,0	8.460,0
4 X 240sm	59,0	9.216,0	11.000,0