



NYCY 0,6/1 kV, CYKIFY 0,6/1 kV

- 0,6/1 kV
- 4 kV
- ( )

DIN VDE 0295 1, 2 IEC 228 1 2

DIN VDE 0207, 5

0,6/1 V / 4 kV

DIN VDE 0295 1 IEC 228 1  
+20 °C

DIN VDE ( )

4 x  
12 x

-40 °C / +70 °C  
- 5 °C / +50 °C

B DIN VDE 0472, 804 IEC 332-1

DIN VDE 0271 IEC 502

n x <sup>2</sup> / /

1 X 10re/10	11,0	216,0	310,0
1 X 16re/16	12,0	336,0	440,0
1 X 25rm/25	16,0	523,0	680,0
2 X 1,5re/1,5	13,0	52,0	210,0
2 X 2,5re/2,5	14,0	80,0	260,0
2 X 4re/4	16,0	123,0	350,0
2 X 6re/6	18,0	182,0	440,0
3 X 1,5re/1,5	14,0	66,0	220,0
3 X 2,5re/2,5	15,0	104,0	290,0
3 X 4re/4	16,0	161,0	400,0
3 X 6re/6	18,0	240,0	500,0
4 X 1,5re/1,5	14,0	81,0	260,0
4 X 2,5re/2,5	15,0	128,0	340,0
4 X 4re/4	17,0	200,0	470,0
4 X 6re/6	19,0	297,0	590,0
4 X 10re/10	21,0	504,0	900,0
5 X 1,5re/1,5	15,0	95,0	320,0
5 X 2,5re/2,5	16,0	152,0	390,0
5 X 4re/4	19,0	238,0	560,0
5 X 6re/6	20,0	355,0	690,0
7 X 4re/4	20,0	315,0	600,0

n x <sup>2</sup> / /

7	X	1,5re/1,5	15,0	124,0	340,0
7	X	1,5re/2,5	16,0	133,0	350,0
8	X	1,5re/2,5	17,0	147,0	460,0
10	X	1,5re/2,5	19,0	176,0	420,0
12	X	1,5re/2,5	20,0	205,0	480,0
14	X	1,5re/2,5	21,0	234,0	530,0
16	X	1,5re/4	22,0	276,0	700,0
19	X	1,5re/4	23,0	320,0	670,0
21	X	1,5re/6	24,0	369,0	950,0
24	X	1,5re/6	26,0	413,0	870,0
30	X	1,5re/6	27,0	499,0	1.250,0
40	X	1,5re/10	30,0	696,0	1.560,0
52	X	1,5re/10	32,0	869,0	1.800,0
61	X	1,5re/10	33,0	998,0	1.950,0
7	X	2,5re/2,5	7,0	200,0	450,0
8	X	2,5re/2,5	18,0	225,0	570,0
10	X	2,5re/4	21,0	286,0	610,0
12	X	2,5re/4	22,0	334,0	670,0
14	X	2,5re/6	23,0	403,0	750,0
16	X	2,5re/6	24,0	451,0	900,0
19	X	2,5re/6	25,0	523,0	950,0
21	X	2,5re/6	26,0	571,0	1.080,0
24	X	2,5re/10	28,0	696,0	1.420,0
30	X	2,5re/10	30,0	840,0	1.600,0
40	X	2,5re/10	33,0	1.080,0	2.000,0
52	X	2,5re/10	38,0	1.368,0	2.500,0